

SECTION 1: Identification : Product identifier and chemical identity

1.1. Product identifier

Product form : Mixture
 Product name : EASYTREAD
 Product code : 3016 - WHITE, 4020 - BLACK, 4161 - SKY BLUE, 4117 - ROYAL BLUE, 4156 - LIGHT GREY, 4129 - TERRA COTTA, 4163 - LIGHT TERRA COTTA, 4016 - FORREST GREEN, 4143 - BRISTOL GREEN, 4140 - MOSS GREEN, 4017 - FERRIC RED

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

No additional information available

1.4. Supplier's details

Endura Paint PTY LTD
 40 Port Kembla Drive
 6163 Bibra Lake - Australia
 T (08) 9418 2999
www.phoenixpaints.com.au

1.5. Emergency phone number

Emergency number : In the event of an emergency involving dangerous goods: Please contact 0429 555 954

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Carcinogenicity, Category 1B H350
 Specific target organ toxicity — Repeated exposure, Category 1 H372

2.2. Label elements

Hazard pictograms (GHS-AU) :



Signal word (GHS-AU) : Danger

Contains : quartz, conc respirable crystalline silica >= 10% (0 - 40 %); quartz, conc respirable crystalline silica >= 10% (0 - 12 %); distillates (petroleum), solvent-refined heavy paraffinic (0.046 - 0.235 %)

Hazard statements (GHS-AU) : H350 - May cause cancer
 H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-AU) : P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
 P264 - Wash thoroughly after handling
 P270 - Do not eat, drink or smoke when using this product.
 P281 - Use personal protective equipment as required.
 P308+P313 - IF exposed or concerned: Get medical advice/attention.
 P314 - Get medical advice/attention if you feel unwell.
 P405 - Store locked up.
 P501 - Dispose of contents/container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

No additional information available

SECTION 3: Composition/Information on ingredients

EASYTREAD

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Name	CAS-No.	Compound type	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
quartz, conc respirable crystalline silica \geq 10%	14808-60-7		0 - 40	STOT RE 1, H372
quartz, conc respirable crystalline silica \geq 10%	14808-60-7		0 - 12	STOT RE 1, H372
distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4		0.046 - 0.235	Carc. 1B, H350

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Take a copy of this safety data sheet when going for medical treatment. IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Remove the victim into fresh air. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : Wash with water and soap. If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water.
- First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately with plenty of water for 15 minutes. Take victim to a doctor/medical service if irritation persists. Rinse eyes with water as a precaution.
- First-aid measures after ingestion : Do not induce vomiting. Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Get immediate medical advice/attention. Never give anything by mouth to an unconscious person. Call a poison center/doctor/physician if you feel unwell.

4.2. Symptoms caused by exposure

- Symptoms/effects after skin contact : May cause an allergic skin reaction. May cause moderate irritation. Itching.
- Symptoms/effects after eye contact : Causes eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

- Other medical advice or treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂). Water spray. Dry powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Do not allow run-off from fire fighting to enter drains or water courses.
- General measures : Avoid contact with skin and eyes. Do not handle until all safety precautions have been read and understood.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Prevent fire-fighting water from entering environment. Use water spray or fog for cooling exposed containers.
- Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
- Other information : On exposure to high temperature, may decompose, releasing toxic gases.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid contact with skin and eyes. Do not handle until all safety precautions have been read and understood.

6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Protective clothing. Protective goggles.

EASYTREAD

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Emergency procedures : Avoid contact with skin and eyes. Wash contaminated clothes. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8 Exposure controls/personal protection".

Emergency procedures : Cover spill with non combustible material, e.g.: sand/earth. Stop leak if safe to do so. Prevent from entering sewers, basements and work pits, or any place where its accumulation can be dangerous.

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter drains or water courses. Do not allow product to spread into the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain large spillage with sand or earth.

Methods for cleaning up : Take up liquid spill into absorbent material. Absorb remaining liquid sand or inert absorbent and remove to safe place. Collect leaking and spilled liquid in sealable containers as far as possible. Scoop absorbed substance into closing containers or synthetic bags. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Notify authorities if product enters sewers or public waters.

SECTION 7: Handling and storage, including how the chemical may be safely used

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin, eyes and clothing. Clean contaminated clothing. Do not discharge the waste into the drain. Do not eat, drink or smoke when using this product. Keep container tightly closed. Observe normal hygiene standards. Use only in well-ventilated areas. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Wear personal protective equipment. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapors/spray.

Hygiene measures : Wash thoroughly after handling. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep cool. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep container tightly closed. Store locked up. Store in a well-ventilated place. Keep cool.

Storage temperature : 10 - 25 °C

Storage area : Protect against frost.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

quartz, conc respirable crystalline silica \geq 10% (14808-60-7)		
USA - ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)

quartz, conc respirable crystalline silica \geq 10% (14808-60-7)		
USA - ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)

Exposure limit values of other components

8.2. Monitoring

No additional information available

EASYTREAD

Safety Data Sheet

according to the Model Work Health and Safety Regulations

8.3. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Personal protective equipment

Hand protection : Gloves. nitrile rubber gloves

Eye protection : Chemical goggles or face shield. Safety glasses

Skin and body protection : Impermeable protective gloves

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Wear approved mask. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Wear respiratory protection.

Environmental exposure controls : Avoid release to the environment.

9.1. SECTION 9: Physical and chemical properties

Physical state : Liquid

Appearance :

Color : No data available

Odor : No data available

Odor threshold : No data available

pH : 7.5 - 8.5

Relative evaporation rate (butyl acetate=1) : No data available

Melting point / Freezing point : Melting point : Not applicable

Boiling point : ≈ 100 °C

Flash point : > 60 °C

Auto-ignition temperature : No data available

Flammability (solid, gas) : No data available

Vapor pressure : No data available

Relative density : No data available

Specific gravity / density : Specific gravity / density : 1.25 g/cm³

Solubility : No data available

Log Pow : No data available

Viscosity : No data available

Explosive properties : No data available

Explosion limits : No data available

Minimum ignition energy : No data available

Fat solubility : No data available

10.1. SECTION 10: Stability and reactivity

Reactivity : The product is non-reactive under normal conditions of use, storage and transport. The product is non-reactive under normal conditions of use, storage and transport

Chemical stability : Stable under normal conditions of use.

Possibility of hazardous reactions : None under normal use.

Conditions to avoid : None under recommended storage and handling conditions (see section 7).

Hazardous decomposition products : No hazardous decomposition products known at room temperature.

11.1. SECTION 11: Toxicological information

Likely routes of exposure : Inhalation. Skin and eyes contact.

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

EASYTREAD

Safety Data Sheet

according to the Model Work Health and Safety Regulations

quartz, conc respirable crystalline silica >=10% (14808-60-7)

LD50 oral rat	> 5000 mg/kg
---------------	--------------

quartz, conc respirable crystalline silica >=10% (14808-60-7)

LD50 oral rat	> 5000 mg/kg
---------------	--------------

Skin corrosion/irritation	: Not classified pH: 7.5 - 8.5
Serious eye damage/irritation	: Not classified pH: 7.5 - 8.5
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

EASYTREAD

Specific gravity / density	1.25 g/cm ³
----------------------------	------------------------

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Aquatic acute	: Not classified
Aquatic chronic	: Not classified

ammonia, conc=2%, aqueous solution (1336-21-6)

Log Pow	-1.14
---------	-------

mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)

LC50 fish 1	0.28 mg/l (LC50; 96 h; Lepomis macrochirus)
EC50 Daphnia 1	0.16 mg/l (EC50; 48 h; Daphnia magna)
Threshold limit algae 1	0.018 mg/l (EC50; 72 h; Pseudokirchneriella subcapitata)

iron(II,III)oxide (1317-61-9)

LC50 fish 1	> 1000 mg/l (LC50; 48 h; Leuciscus idus)
-------------	--

pentapotassium triphosphate (13845-36-8)

LC50 fish 1	> 800 mg/l (LC50; 48 h; Leuciscus idus)
-------------	---

tetrapotassium pyrophosphate, anhydrous (7320-34-5)

LC50 fish 1	> 750 mg/l (LC50; 48 h)
-------------	-------------------------

dipotassium hydrogen phosphate, anhydrous (7758-11-4)

LC50 fish 1	> 900 mg/l (LC50; 48 h; Leuciscus idus)
-------------	---

magnesium nitrate (10377-60-3)

LC50 fish 1	1378 mg/l (LC50; Equivalent or similar to OECD 203; 96 h; Poecilia reticulata; Static system; Fresh water; Read-across)
EC50 Daphnia 1	490 mg/l (EC50; 48 h; Daphnia magna)
Log Pow	-0.61 (Estimated value)
Threshold limit algae 1	> 1700 mg/l (EC50; 10 days; Nitzschia closterium)

copper(II) nitrate (3251-23-8)

LC50 fish 2	0.25 mg/l (LC50; 96 h)
EC50 other aquatic organisms 1	0.085 mg/l (336 h; Selenastrum capricornutum)

EASYTREAD

Safety Data Sheet

according to the Model Work Health and Safety Regulations

copper(II) nitrate (3251-23-8)	
BCF fish 1	200 - 667 (BCF)
BCF other aquatic organisms 1	471 (BCF; 168 h; Daphnia magna)
BCF other aquatic organisms 2	2400 (BCF; 168 h; Daphnia magna)
4-nonylphenol, branched, ethoxylated (127087-87-0)	
EC50 Daphnia 1	1000 mg/l (LC50; 48 h; Crustacea)
zinc oxide (1314-13-2)	
EC50 Daphnia 2	0.33 - 0.66 mg/l (LC50; Equivalent or similar to OECD 202; 48 h; Daphnia magna; Static system; Fresh water; Read-across)
Log Pow	1.53 (Estimated value)
Log Koc	log Koc,2.2; Literature study
Threshold limit algae 1	0.136 mg/l (IC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)
dibutyl phthalate (84-74-2)	
LC50 fish 1	0.85 ppm (LC50; 96 h)
EC50 Daphnia 2	3.1 - 3.8 mg/l (EC50; 48 h)
EC50 other aquatic organisms 1	9 mg/l (48 h; Scenedesmus subspicatus; Growth rate)
BCF fish 1	12 (BCF)
BCF fish 2	117 (BCF)
BCF other aquatic organisms 1	22 - 42 (BCF)
BCF other aquatic organisms 2	5000 (BCF; 72 h)
Log Pow	3.23 - 5.6
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate (25265-77-4)	
LC50 fish 1	30 mg/l (LC50; 96 h; Pimephales promelas)
EC50 Daphnia 1	147.8 mg/l (EC50; 48 h)
Log Pow	3.47 (Experimental value)
Threshold limit algae 2	18.4 mg/l (EC50; 72 h)
petroleum extracts,light paraffinic distillate solvent (64742-05-8)	
Log Pow	4.4 - 6 (Calculated)
carbon black (1333-86-4)	
LC50 fish 1	> 1000 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Brachydanio rerio)
LC50 fish 2	1000 mg/l (LC0; OECD 203: Fish, Acute Toxicity Test; 96 h; Brachydanio rerio; Semi-static system; Fresh water; Experimental value)
EC50 Daphnia 1	> 5600 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 24 h; Daphnia magna; Static system; Fresh water)
Threshold limit algae 1	> 10000 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Scenedesmus subspicatus; Static system; Fresh water; Experimental value)
talc (14807-96-6)	
LC50 fish 1	> 100 g/l (LC50; 24 h; Brachydanio rerio)
zinc oxide (1314-13-2)	
EC50 Daphnia 2	0.33 - 0.66 mg/l (LC50; Equivalent or similar to OECD 202; 48 h; Daphnia magna; Static system; Fresh water; Read-across)
Log Pow	1.53 (Estimated value)
Log Koc	log Koc,2.2; Literature study
Threshold limit algae 1	0.136 mg/l (IC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)
sulfur, solid (7704-34-9)	
LC50 fish 1	866 mg/l (LC50; 96 h; Brachydanio rerio)
EC50 Daphnia 1	> 100 mg/l (LC50; 48 h)
Log Pow	0.23 (Estimated value)
titanium(IV) oxide (13463-67-7)	
EC50 Daphnia 1	> 100 mg/l (LC50; Equivalent or similar to OECD 202; 48 h; Daphnia magna; Static system; Fresh water; Weight of evidence)
Threshold limit algae 1	61 mg/l (EC50; Other; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)

EASYTREAD

Safety Data Sheet

according to the Model Work Health and Safety Regulations

polyethylene glycol monooleate (9004-96-0)	
EC50 Daphnia 1	170 mg/l (EC50; 48 h)
2,6-di-tert-butyl-p-cresol (128-37-0)	
LC50 fish 1	>= 0.57 mg/l (LC0; EU Method C.1; 96 h; Brachydanio rerio; Semi-static system; Fresh water; Experimental value)
LC50 fish 2	0.199 mg/l (LC50; ECOSAR v1.00; 96 h; Pisces)
EC50 Daphnia 1	0.48 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
EC50 Daphnia 2	0.15 mg/l (NOEC; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
BCF fish 1	230 - 2500 (BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 56 days; Cyprinus carpio; Flow-through system; Fresh water; Experimental value)
Log Pow	5.1 (Experimental value)
Log Koc	Koc,PCKOCWIN v1.66; 23030; Calculated value; log Koc; PCKOCWIN v1.66; 4.362; Calculated value
diethylene glycol (111-46-6)	
LC50 fish 1	> 5000 ppm (LC50; 24 h)
EC50 Daphnia 1	> 10000 mg/l (EC50; 24 h)
BCF fish 1	100 (BCF; Other; 3 days; Leuciscus melanotus; Static system; Fresh water; Experimental value)
Log Pow	-1.98 (Calculated; Other)
Log Koc	Koc, SRC PCKOCWIN v1.66; 1; Calculated value; log Koc; SRC PCKOCWIN v1.66; 0; Calculated value
C.I. pigment blue 15 (147-14-8)	
LC50 fish 2	> 500 mg/l (LC50; 96 h)
BCF fish 1	< 11 (BCF)
Log Pow	6.6
talc (14807-96-6)	
LC50 fish 1	> 100 g/l (LC50; 24 h; Brachydanio rerio)
titanium(IV) oxide (13463-67-7)	
EC50 Daphnia 1	> 100 mg/l (LC50; Equivalent or similar to OECD 202; 48 h; Daphnia magna; Static system; Fresh water; Weight of evidence)
Threshold limit algae 1	61 mg/l (EC50; Other; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)
iron(III) oxide (1309-37-1)	
LC50 fish 1	> 1000 mg/l (LC50; 48 h)
chromium(III) oxide (1308-38-9)	
LC50 fish 1	> 2.9 µg/l (LC50; ISO 7346-1; 96 h; Danio rerio; Static system; Fresh water; Experimental value)
BCF fish 1	260 - 800 (BCF; Lepomis macrochirus)
BCF other aquatic organisms 1	116 (BCF)
BCF other aquatic organisms 2	86 (BCF)
Threshold limit algae 1	> 848.6 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Desmodesmus subspicatus; Static system; Fresh water; Read-across)
quartz, conc respirable crystalline silica>=10% (14808-60-7)	
LC50 fish 1	> 500 mg/l
EC50 Daphnia 1	> 300 mg/l
quartz, conc respirable crystalline silica>=10% (14808-60-7)	
LC50 fish 1	> 500 mg/l
EC50 Daphnia 1	> 300 mg/l
iron(III) oxide (1309-37-1)	
LC50 fish 1	> 1000 mg/l (LC50; 48 h)
barium sulfate (7727-43-7)	
EC50 Daphnia 1	32 mg/l (EC50; 48 h)
BCF fish 1	68.4 (BCF; Lepomis macrochirus)

EASYTREAD

Safety Data Sheet

according to the Model Work Health and Safety Regulations

barium sulfate (7727-43-7)	
Threshold limit algae 1	≥1.92,NOEC; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value

12.2. Persistence and degradability

quartz, conc respirable crystalline silica>=10% (14808-60-7)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

quartz, conc respirable crystalline silica>=10% (14808-60-7)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available

EASYTREAD	
Fluorinated greenhouse gases	False

distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)	
Fluorinated greenhouse gases	False

quartz, conc respirable crystalline silica>=10% (14808-60-7)	
Fluorinated greenhouse gases	False

quartz, conc respirable crystalline silica>=10% (14808-60-7)	
Fluorinated greenhouse gases	False

SECTION 13: Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Dispose of contents/container in accordance with all local, regional, national and international regulations.

SECTION 14: Transport information

14.1. UN number

Not regulated for transport

14.2. Proper Shipping Name - Addition

Not applicable

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

EASYTREAD

Safety Data Sheet

according to the Model Work Health and Safety Regulations

14.4. Packing group

Packing group (ADG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Marine pollutant : No

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

14.8. Hazchem or Emergency Action Code

Hazchemcode : Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Listed on the AICS (the Australian Inventory of Chemical Substances) : Listed on the AICS (the Australian Inventory of Chemical Substances)

15.2. International agreements

No additional information available

SECTION 16: Any other relevant information

Revision date : 20/03/2019

Classification:

Carc. 1B	H350
STOT RE 1	H372

Full text of H-phrases:

Carc. 1B	Carcinogenicity Category 1B
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure

SDS Australia (Phoenix)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product